arXiv:1211.6406v1 [math.OC] 27 Nov 2012

Simulation model for assembly lines with heterogeneous workers

Pedro B. Castellucci and Alysson M. Costa

Instituto de Ciências Matemáticas e de Computação, Universidade de São Paulo
Av. Trabalhador São-Carlense, 400 Cx. Postal 668 - São Carlos-SP - CEP 13560-970
pedrocastellucci@gmail.com; alysson@icmc.usp.br

Abstract

An interesting empirical result in the assembly line literature states that slightly unbalanced assembly lines (in the format of a bowl - with central stations less loaded than the external ones) present higher throughputs than perfectly balanced ones. This effect is known as the *bowl phenomenon*. In this study, we analyze the presence of this phenomenon in assembly lines with heterogeneous workers (most of them, workers with disabilities). For this purpose, we modify an existing model for the *assembly line worker assignment and balancing problem* in order to generate configurations exhibiting the desired format. These configurations are implemented in a stochastic simulation model and the obtained results are analyzed. The findings obtained here confirm the existence of the bowl phenomenon in such situations and contributes to deepen our knowledge in this empirical phenomenon.

Keywords: Assembly lines, simulation, disabled workers, heterogenous workers, bowl phenomenon.

1 Introduction

Assembly lines are productive systems specially useful for large scale standardized manufacturing. The main rationale behind such systems is labour division. This is done by dividing the tasks to be executed among a number of workers or workstations (Scholl 1999). In each workstation, a subset of the tasks is executed. The most classical assembly line balancing problem is known as SALBP (*simple assembly line balancing problem*) and considers, among other hypotheses, that all workers/workstations are equally efficient. A large amount of research has been done on the SALBP and includes both classical and recent surveys and research articles (Salveson 1955, Tonge 1961, Baybars 1986, Ghosh & Gagnon 1989, Scholl 1999, Scholl & Becker 2006, Boysen & Fliedner 2008, Scholl et al. 2010).

SALBP's hypotheses are rarely valid in practical contexts. This fact has motivated the study of a large number of its variants (Boysen et al. 2007, Boysen et al. 2008, **?**) . In particular, this research addresses the case of assembly lines in sheltered work centers for disabled. In this case, due to workers heterogeneity, task execution times depend on the worker they are assigned to. This gives origin to a problem in which, besides assigning tasks to workstations, there is also the need to assign workers to workstations. This situation has been first modelled by Miralles et al. (2007) and named ALWABP (*assembly line worker assignment and balancing problem*).

Both SALBP and ALWABP assume deterministic execution times for each task and, hence, the line's throughput is dictated by the most loaded workstation. In practice, however, task execution times are usually stochastic. This may occur due to small differences among parts, changes in worker's behaviour, technical issues and many other random events. The randomness in execution times may lead to interesting effects such as the well known bowl phenomenon, in which slightly unbalanced lines in the format of a bowl, i.e., with central workstations less loaded), or with central workstations with more stable loads (less variable execution times), have a better productivity (Hillier & Boling 1966).

The theory behind the Bowl phenomenon is not yet fully understood. Nevertheless, the effect may lead to adjustments in optimization methods (heuristic and exact) in order to enhance throughput of assembly lines in practical contexts. Thereunto, simulation models are helpful, because they allow the modelling of execution times with higher precision.

In this study, an assembly line simulation model for productivity analysis is proposed. In particular, the interest is in the ALWABP case, for which no similar study has been developed to the best of the authors knowledge. The main goal is to verify the bowl phenomenon in assembly lines with heterogeneous workers. For this purpose, a mixed-integer programming model capable of supplying solutions with unbalanced bowl-shaped profiles (with greater or lesser slope) is proposed. These solutions are used as parameters in the simulation model, also developed in this work, and the results are discussed.

The remainder of this article is organized as follows. In the following section, the ALWABP problem and model are presented. Also in this section, this model is modified in order to generate solutions with unbalanced bowl-shaped profiles. Then, Section 3 focus on the proposed simulation model development while Section 4 presents the computational experiments and results. General conclusions end this paper in Section 5.

2 ALWABP

Miralles et al. (2007) have proposed the ALWABP motivated by the situation found in sheltered work centers for the disabled, in which assembly lines are operated with disabled workers. This problem has fomented an intense amount of research both on the original problem (Miralles et al. 2008, Chaves et al. 2009, Moreira et al. 2012) and on some of its variants (Costa & Miralles 2009, Cortez & Costa 2011, Araújo et al. 2012, **?**).

In order to model the ALWABP, let N be a set of tasks. The execution time of each task $i \in N$ depends on the worker it is assigned to and is assumed deterministic. Indeed, p_{wi} is the executing time of task i by worker w. Tasks $i \in N$ must respect a partial ordering. We use the notation $i \lessdot j$ to indicate that task i must be completed before task j is initiated. Also, let W represent all workers available and S represent the set of workstations. Defining binary variables y_{sw} (equal to 1 if, and only if, worker $w \in W$ is allocated to station $s \in S$) and variables x_{swi} (equal to 1 if, and only if, task $i \in N$ is executed at station $s \in S$ by worker $w \in W$) and a variable C representing the cycle time (execution time of the most loaded workstation), the ALWABP can be written as:

$$\text{Min } C \tag{1}$$

subjected to:

$$\sum_{s \in S} \sum_{w \in W} x_{swi} = 1, \qquad \forall i \in N, \tag{2}$$

$$\sum_{s \in S} y_{sw} = 1, \qquad \forall w \in W, \tag{3}$$

$$\sum_{w \in W} y_{sw} = 1, \qquad \forall s \in S, \tag{4}$$

$$\sum_{s \in S} \sum_{w \in W} s \cdot x_{swi} \leq \sum_{s \in S} \sum_{w \in W} s \cdot x_{swj}, \qquad \forall i, j \in N, i \lessdot j, \tag{5}$$

$$\sum_{i \in N} \sum_{w \in W} p_{wi} \cdot x_{swi} \leq C, \qquad \forall s \in S, \tag{6}$$

$$\sum_{i \in N} x_{swi} \leq |N| y_{sw}, \qquad \forall s \in S, \forall w \in W, \tag{7}$$

$$y_{sw} \in \{0, 1\}, \qquad \forall s \in S, \forall w \in W, \tag{8}$$

$$x_{swi} \in \{0, 1\}, \qquad \forall s \in S, \forall w \in W, \forall i \in N. \tag{9}$$

The the goal of model (1)-(9) is to obtain worker and task assignments to the workstations so that the cicle time is minimized. Constraints (2) force every task to be executed, while (3) and (4) guarantee that each worker is assigned to a workstation and each workstation receives a single worker, respectively. The task execution partial ordering is respected due to constraints (5), while (6) define the line's cycle time. Finally, constraints (7) make ensure that a task is executed by a worker in a given workstation only if the worker is assigned to the workstation.

2.1 The bowl phenomenon and the ALWABP

Manly in non-automatized assembly lines, where people, not machines, are responsible for doing the tasks, the execution times are not deterministic. Thus, production rate depends on the distribution dictating the task times. It was realized (Hillier & Boling 1966) that if the operation times (task times) were following an exponential distribution, then the assembly line throughput could be enhanced by introducing specific small load unbalances. This effect became know as the *bowl phenomenon*, since the graphic of total time of each workstation along the line has the shape of a bowl, with times increasing from central station(s). Figure 1 shows an example of such configuration in a line with 8 workstations.



Figure 1: Example of a bowl profile.

There is an equivalent of the bowl phenomenon which happens regarding buffers capacity placed between the workstations. An assembly line's throughput can be enhanced by placing buffers with a slightly larger capacity between central stations (Hillier 1993). Hillier (1993) presents numerical results, expanding the findings from (Hillier 1979), which were only available for small lines. These results show that, for many cases, with bowl allocation, there can be nearly a 1% raise in line's throughput, up to a 2% enhance. This result gradually decrease with the increase of buffer capacities and with the reduction of the variation coefficient C, defined as $C = \frac{\mu}{\sigma}$, in which μ is the task execution time distribution mean and σ its standard deviation. Finally, Hillier (1996) also analyzed the robustness of the effect, concluding that bowl-shaped lined provided better results than complete balanced assembly lines even with relatively large deviations with respect to the "ideal" bowl format.

In this work, we try to conclude the existence of the bowl effect in lines with a heterogeneous workforce. in order to do so, the first step is to generate solutions respecting the bowl load profile (Figure 1). This was done in two ways with two different objectives. This first strategy generates bowl-like solutions in order to study the phenomenon considering workstation load. The second one also targets the obtention of the bowl effect but focus on the execution times deviations: tasks with less variable times are assigned to central stations. These two approaches are presented in the following subsections.

2.1.1 Load unbalance

Constraints (6) are appropriate for the deterministic scenario because they induce a uniform load distribution among all workstations, hence minimizing the cicle time C. In order to obtain bowl-like solutions, these restrictions are modified as follows:

$$\sum_{i \in N} \sum_{w \in W} p_{wi} \cdot x_{swi} \leq \alpha_s C, \qquad \forall s \in S, \tag{10}$$

in which α_s are parameters whose values respect the following equations:

$$\alpha_1 > 0, \tag{11}$$

$$\alpha_s = \alpha_{|S|-s+1}, \qquad s = 1 \dots \lfloor |S|/2 \rfloor. \tag{12}$$

$$\alpha_s = \beta \alpha_{s-1}, \qquad s = 2 \dots \lfloor |S|/2 \rfloor - 1. \tag{13}$$

Constraints (11) guarantee positive loads for workstations while constraints (12) induce symmetry in the load configuration. Finally, constraints (13) define the bowl slope level which is controlled by parameter β, $0 \leq \beta \leq 1$. Figure 2 shows examples of resulting profiles for some values of α and β.



Figure 2: Load configurations for different parameters α and β.

2.1.2 Deviation unbalance

Other characteristic that may induce a bowl effect is related to task times deviations. Let $c_s = \frac{\mu}{\sigma}$ indicate the level of variability in a given station execution time $s \in S$. An inverse bowl profile is obtained by maintaining the station loads fixed and reducing the task deviation times in central stations. The variation was computed considering solutions without restrictions (10) and by artificially adjusting task deviation times from the base case.

For five stations, the balanced case ($c_s = 10, s = 1, .., 5$) was modified by increasing parameter c_3 by a unit. This change was conpensated with a 0.5 reduction in each extreme workstation, keeping the total load and simmetry of the line unchanged. Similarly, for six stations c_3 and c_4 have a unity raise and c_1 and c_6 have a unit reduction; and, for seven workstations, c_4 has a unity raise and c_1 and c_7 have a 0.5 reduction.

3 Simulation Model

Simulation is a technique for performance and reaction analysis of a system. It can be useful both in planning stages or when the system is already in operation if careful validation on practical contexts is effected (**?**). Most benefits of simulation appear in contexts in which the system under study has many features that can not be modeled properly with the use of other analytical techniques due, for example, to its complexity.

When building a simulation model, it is important to define the inputs and outputs so the results may be analyzed. This analysis depends on the nature of the model. If the model is deterministic, for example, the model only have to run once for each input one may want to analyze; on the other hand, in a stochastic model, it is possible to use a Monte Carlo method: the essence of it is to use stochastic distributions, each one representing a process in the model. Then, a statiscal sampling is used to summarize the result for each input. In other words, it can be used to analyze process which have a degree of uncertanty (randomness) in the variables (Kroese 2008).

The simulation model built in order to evaluate assembly lines in this work has the number of products which left the line as a state-variable, it is of continuous time, discrete state, stochastic, linear, dinamic, open and unstable (Ross 2006). The system has been modeled with the commercial simulation general-purpose software **Goldsim** (Goldsim 2010). A schematic representation of the model build is presented in figures 3 and 4, which show the external control (responsible for controlling the flow of unities between stations) and the internal control (responsible for defining the time the unity is processed in each station), respectively.



Figure 3: External control.



Figure 4: Internal control.

The external control ensures that there is always a piece available for the first station, this is done with the event *new_product* which draws unities from an infinite buffer (*buffer_0_1*). The product is put into unit buffers so it can be passed from a previous station to a following one. It is important to state that these are not real buffers: the product is put in and removed from them in the same moment (the buffers are used only for implementational issues). The final buffer *number_of_products* stores the number of produced unities during simulation. Elements *Machine1*, *Machine2* and *Machine3* represent workstations and are there to encapsulate the internal logical control of each station.

The internal control was constructed in the following way: there is a delay (*machine_delay1*) whose value is the sum of individual task execution times (which depend on the worker assigned to the station). This delay will determine how long the piece will stay in that station. The workstation has a status (*machine_ready1)*, which is either *ready*, in case it is ready to receive another piece, or *busy*, if the station is processing a piece. There are also three possible events: *pick from buffer* (*pick_from_buffer_1*), *put in buffer* (*put_in_buffer_1*) and *delay* (*machine_delay1*). When a product/piece is withdrawn from a previous buffer (*pick from buffer* event) the *status* is changed from *ready* to *busy* and a *delay* event is generated. After the delay has been processed, if the following workstation has a *ready* status, an event *put in buffer* is generated, otherwise the event waits until the following station is ready to process it.

As mentioned, the total value of the delay (*machine_delay1*) depends on values of *task time* events associated to it. In this study we use a stochastic simulation and these elements are configured with two parameters: mean and standard deviation. Both are obtained from solutions generated with the mathematical model presented in Section 2. The solution is schematically depicted in Figure 5.


Precedence graph
Workers
Workstations
Deterministic Mathematical Model
Allocation
Each task mean execution time
Each task standard deviaton time
Stochastic Simulation Model
Production

Figure 5: Scheme for obtaining computational results.

The mathematical model's inputs are: the precedence graph, which determines the order in which tasks must be executed; workers, indicating how long each worker takes to accomplish each one of the possible tasks; and the number of available workstations. The model's solution is a possible assignment of workers and tasks to workstations. This allocation leads to simulation parameters, more specifically, the values (mean and standard deviation) of *taks_time* elements which are summed in a *machine_time* element. With these parameters, the simulation model may compute the assembly line stochastic throughput.

4 Computational results

The computational results were obtained with a series of stochastic simulations using a Monte Carlo method. Each input was ran 250 times in order to obtain a statistically relevant results. Execution times were assumed to follow a Normal distribution, $N(\mu, \sigma^2)$, with mean μ and variance σ^2, μ being the deterministic value and $\sigma = \frac{\mu}{10}$ in simulations in which the mean was the variable of interest.

In order to obtain results related to the mean, parameter β from equation (13) was slowly reduced in central stations until a solution became different from the previous one, this characterize a new depth bowl level to be analyzed. Parameter α_s from equations (10) were chosen so that a more strict time restriction in central workstations implies more flexible times on external workstations. For each combination of α_s and β, the modified mathematical model was solved. The resulting solution defined tasks and workers assignments in the simulation model. The results, considering line productivity for each level studied, are shown in Table 1. These tests were done using classical instances found in the literature (Chaves et al. 2009). The best solutions of each case are bold marked. Table 2 discriminates the load for each station in the best solutions, shown in Table 1, and the corresponding throughput enhancement.

Table 1: Results for unbalances on mean loads.

	Unbalance						
Instance	**level 0**	**level 1**	**level 2**	**level 3**	**level 4**	**level 5**	**level 6**
HESKIA 01	144.310	**144.580**	143.750	142.870	142.890	139.270	138.190
HESKIA 11	78.804	73.572	78.760	**79.016**	78.864	78.596	77.248
HESKIA 21	66.004	**66.960**	66.012	65.696	65.696	65.140	63.916
HESKIA 31	64.592	65.076	63.968	**65.280**	64.832	65.096	64.272
HESKIA 41	389.250	390.040	390.020	395.710	**403.460**	392.000	383.900
HESKIA 51	275.010	271.500	276.760	**276.880**	270.840	275.920	276.100
HESKIA 61	203.700	204.660	**206.460**	204.670	205.910	205.520	203.380
HESKIA 71	**150.530**	147.840	149.510	148.660	148.660	149.350	145.860
ROSZIEG 01	**712.790**	704.490	687.430	593.570	677.650	675.470	646.990
ROSZIEG 11	**475.780**	457.830	420.130	420.250	420.120	420.070	420.080
ROSZIEG 21	**495.350**	459.630	459.490	445.550	459.590	431.840	431.700
ROSZIEG 31	456.610	456.490	456.260	**456.740**	456.570	429.640	419.140
ROSZIEG 41	1371.300	1406.900	**1411.700**	1402.500	1376.300	1406.000	1369.200
ROSZIEG 51	1251.300	1286.000	1277.000	1276.200	1286.000	**1286.900**	1277.500
ROSZIEG 61	854.430	**874.370**	832.770	832.550	832.800	826.340	832.800
ROSZIEG 71	914.640	**937.640**	920.960	935.400	868.460	872.100	880.850

It can be seen (Table 1) that balanced solutions (level 0) are only the most efficient configurations in a few cases (instance 71 from the Heskia family and instances 01, 11 and 21 from the Roszieg family). For the other instances, different levels of unbalance presented the best results. On the other hand, Table 2 shows that the obtained solutions are not perfect bowl-shaped, this happens because tasks are not divisible so a smooth bowl-shaped solution cannot be guaranteed. Examples of good and bad bowl shaped formats can be found in instances Heskia 11 and Heskia 61, respectively. Nevertheless, confirming the robustness of the bowl effect predicted by Hillier (1996), both cases presented productivity improvements with respect to the balanced case.

Table 2: Station loads for optimal results.

Instance	Load-1	Load-2	Load-3	Load-4	Load-5	Load-6	Load-7	Increase
HESKIA 01	93	94	92	94	-	-	-	0.19%
HESKIA 11	172	160	161	172	-	-	-	0.27%
HESKIA 21	202	183	196	199	-	-	-	1.45%
HESKIA 31	206	197	194	206	-	-	-	1.07%
HESKIA 41	33	35	30	33	30	33	32	3.65%
HESKIA 51	51	34	31	36	39	46	48	0.68%
HESKIA 61	62	64	48	64	66	61	50	1.35%
HESKIA 71	90	61	91	66	82	86	84	0.00%
ROSZIEG 01	17	20	17	16	-	-	-	0.00%
ROSZIEG 11	29	3	30	19	-	-	-	0.00%
ROSZIEG 21	25	27	28	28	-	-	-	0.00%
ROSZIEG 31	31	29	23	31	-	-	-	0.03%
ROSZIEG 41	5	10	7	9	9	8	-	2.95%
ROSZIEG 51	7	11	9	9	9	7	-	2.85%
ROSZIEG 61	12	15	15	15	15	16	-	2.33%
ROSZIEG 71	11	9	12	15	11	15	-	2.51%

The best enhancement in throughput was obtained in instances Heskia 41, in which a 3.65% increase in throughput could be observed in comparison to the standard balanced case. Figure 6 shows how throughput (vertical axis) evolves as a function of the level (horizontal axis) for Heskia 41; the points were connected to emphasize the behaviour around the best solution obtained. In general, the curve smoothness cannot be guaranteed due to the indivisibility of tasks to be allocated.



Figure 6: Throughput graphic as function of bowl depth for mean.

The results showing how the assembly line is affected for cases in which central execution times are less variable than those in the line's extremes are in Table 3. Considering instances with tasks with greater deviation on peripheral workstations, the bowl phenomenon appeared not as often as in the previous case. Nevertheless, the effect could be observed in some instances.

Table 3: Results for unbalances in U values.

	Unbalance						
Instance	**level 0**	**level 1**	**level 2**	**level 3**	**level 4**	**level 5**	**level 6**
HESKIA 01	**144.310**	144.010	143.560	142.810	141.800	140.390	138.140
HESKIA 11	**78.800**	78.570	78.350	78.000	77.500	76.692	75.658
HESKIA 21	**66.000**	65.980	65.860	65.550	65.120	64.560	63.708
HESKIA 31	**64.590**	64.600	64.470	64.210	63.896	63.428	62.724
HESKIA 41	**389.250**	388.450	387.460	386.040	384.120	381.510	377.130
HESKIA 51	**275.010**	274.480	273.810	272.860	271.520	269.570	266.500
HESKIA 61	203.700	203.750	204.280	204.660	**204.910**	204.580	203.220
HESKIA 71	**150.530**	150.410	150.390	150.190	149.630	149.000	147.580
ROSZIEG 01	**712.790**	712.560	712.390	712.190	712.020	711.760	710.080
ROSZIEG 11	475.780	475.800	475.820	**475.870**	475.790	475.790	475.680
ROSZIEG 21	**495.350**	494.860	493.820	492.800	490.320	487.000	481.970
ROSZIEG 31	**456.510**	455.810	454.900	453.620	451.800	449.470	445.750
ROSZIEG 41	1371.300	1373.100	1374.400	1375.300	**1375.400**	1374.300	1370.100
ROSZIEG 51	1251.300	1252.400	**1252.800**	1252.500	1250.800	1246.600	1238.000
ROSZIEG 61	**854.430**	853.700	852.200	849.800	846.400	841.170	832.020
ROSZIEG 71	914.640	916.060	917.200	918.100	918.760	**919.120**	918.880

Table 4 details the line configuration of the best solution found for each instance (associated with the bold value in each line of Table 3). The table lists the load of each station and the value of the $U = \mu/\sigma$ parameter (determined according to section 2). The greater enhancement in throughput was 0.6% comparing to balanced case. This happened in a 4 unit unbalance, i.e., with parameters U_3 and U_4 (central stations in Heskia 61) raised by four units.



Figure 7: Throughput graphic as a function of bowl depth for standard deviation.

Figure 7 depicts how assembly line's throughput evolves related to level of unbalance for HESKIA 61. The points were connected to emphasize function behaviour around the best solution found. This curve tends to be smoother than the one presented on Figure 6 because raising the unbalance, parameter

Table 4: Details for U unbalance.

Instance		**S1**	**S2**	**S3**	**S4**	**S5**	**S6**	**S7**	**Increase**
HESKIA 01	Load	93	94	92	94	-	-	-	0.00 %
	U	10	10	10	10	-	-	-	
HESKIA 11	Load	168	168	169	169	-	-	-	0.00%
	U	10	10	10	10	-	-	-	
HESKIA 21	Load	200	200	199	200	-	-	-	0.00%
	U	10	10	10	10	-	-	-	
HESKIA 31	Load	204	203	204	204	-	-	-	0.00%
	U	10	10	10	10	-	-	-	
HESKIA 41	Load	33	35	34	31	29	35	35	0.00%
	U	10	10	10	10	10	10	10	
HESKIA 51	Load	51	48	40	33	36	40	49	0.00%
	U	10	10	10	10	10	10	10	
HESKIA 61	Load	60	61	62	66	66	59	57	0.59%
	U	6	10	12	14	12	10	6	
HESKIA 71	Load	90	61	91	66	82	86	84	0.00%
	U	10	10	10	10	10	10	10	
ROSZIEG 01	Load	17	20	17	16	-	-	-	0.00%
	U	0	0	0	0	-	-	-	
ROSZIEG 11	Load	29	3	30	19	-	-	-	0.02%
	U	7	13	13	7	-	-	-	
ROSZIEG 21	Load	25	27	28	28	-	-	-	0.00%
	U	10	10	10	10	-	-	-	
ROSZIEG 31	Load	31	30	26	23	-	-	-	0.00%
	U	6	10	12	14	-	-	-	
ROSZIEG 41	Load	7	10	10	9	10	9	-	0.30%
	U	6	10	14	14	10	6	-	
ROSZIEG 51	Load	6	11	10	11	11	10	-	0.11%
	U	5	10	15	15	10	5	-	
ROSZIEG 61	Load	12	14	16	15	16	16	-	0.00%
	U	10	10	10	10	10	-	-	
ROSZIEG 71	Load	11	9	14	15	15	12	-	0.50%
	U	5	10	15	15	10	5	-	

U, does not imply a possible task reallocation; this happens in the mean case because it is more closely related with the solution obtained from the mathematical model which is restricted by parameter α of constraints (10).

5 Conclusions

This study introduced a mixed-integer mathematical model to obtain slightly unbalanced load profiles for assembly lines with heterogeneous workers. These profiles were used in a simulation model to verify that the efficiency of the lines could be improved if they were slightly unbalanced. These results expand the scope of the well-known bowl phenomenon, which is empirically know since the sixties but whose theoretical causes are yet not very well explained. We believe this simple study somehow reopen some questions on this classical phenomenon and encourages new research on its effect on lines with heterogeneous resources.

6 Acknowledgments

This work was developed with financial support from CNPq, CAPES/DGU (258-12) and FAPESP.

References

Araújo, F. F. B., Costa, A. M. & Miralles, C. (2012). Two extensions for the assembly line worker assignment and balancing problem: parallel stations and collaborative approach., *International Journal of Production Economics (accepted)* .

Baybars, I. (1986). A Survey of Exact Algorithms for the Simple Assembly Line Balancing Problem, *Management Science* **32**: 909–932.

Boysen, N. & Fliedner, M. (2008). A versatile algorithm for assembly line balancing, *European Journal of Operational Research* **184**: 39–56.
URL: *http://linkinghub.elsevier.com/retrieve/pii/S0377221706011362*

Boysen, N., Fliedner, M. & Scholl, A. (2007). A classification of assembly line balancing problems, *European Journal of Operational Research* **183**: 674–693.

Boysen, N., Fliedner, M. & Scholl, A. (2008). Assembly line balancing: Which model to use when?, *International Journal of Production Economics* **111**: 509–528.

Chaves, A. A., Lorena, L. A. N. & Miralles, C. (2009). Hybrid metaheuristic for the assembly line worker assignment and balancing problem, *Lecture Notes on Computer Science* **5818**: 1–14.

Cortez, P. M. C. & Costa, A. M. (2011). A mathematical model and a hybrid heuristic for sequencing mixed-model assembly lines with disabled workers, *Anais do XLIII Simpósio Brasileiro de Pesquisa Operacional*, Ubatuba.

Costa, A. M. & Miralles, C. (2009). Job rotation in assembly lines employing disabled workers, *International Journal of Production Economics* **120**: 625–632.

Ghosh, S. & Gagnon, R. J. (1989). A comprehensive literature review and analysis of the design, balancing and scheduling of assembly systems, *International Journal of Production Research* **27**: 637–670.

Goldsim (2010). *Goldsim Users Manual, Volumes 1 - 2*.

Hillier, F. S. & Boling, R. W. (1966). The effects of some design factors on the efficiency of production lines with variable operation times., *Journal of Industrial Engineering* **17**: 651–658.

Hillier, F. S.; So, K. C. (1979). On optimal allocation of work in symmetrically unbalanced production line system with variable operation times, *Managemente Science* **198-206**.

Hillier, F. S.; So, K. C. (1993). Towards characterizing the optimal allocation of storage space in production line systems with variable processing times., *Management Science* pp. 126–133.

Hillier, F. S.; So, K. C. (1996). On the robustness of the bowl phenomenon, *European Journal of Operational Research* pp. 496–515.

Jain, R. (1991). *The Art of Computer Systems Performance Analysis: Techniques for Experimental Design, Measurement, Simulation, and Modeling*.

Kroese, R. Y. R. D. P. (2008). *Simulation and The Monte Carlo Method*, 2nd edn, John Wiley & Sons, Inc.

Miralles, C., Garcia-Sabater, J. P., Andrés, C. & Cardos, M. (2007). Advantages of assembly lines in Sheltered Work Centres for Disabled. A case study, *International Journal of Production Economics* **110**: 187–197.

Miralles, C., Garcia-Sabater, J. P., Andrés, C. & Cardos, M. (2008). Branch and bound procedures for solving the Assembly Line Worker Assignment and Balancing Problem: Application to Sheltered Work centres for Disabled, *Discrete Applied Mathematics* **156**: 352–367.

Moreira, M. C. O., Ritt, M., Costa, A. M. & Chaves, A. A. (2012). Simple heuristics for the assembly line worker assignment and balancing problem, *Journal of heuristics* **18**: 505–524.

Ross, S. M. (2006). *Simulation*, Elsevier.

Salveson, M. E. (1955). The assembly line balancing problem, *Journal of Industrial Engineering* **6**: 18–25.

Scholl, A. (1999). *Balancing and sequencing of assembly lines*, Physica-Verlag.

Scholl, A. & Becker, C. (2006). State-of-the-art exact and heuristic solution procedures for simple assembly line balancing, *European Journal of Operational Research* **168**: 666–693.

Scholl, A., Fliedner, M. & Boysen, N. (2010). Absalom: Balancing assembly lines with assignment restrictions, *European Journal of Operational Research* **200**: 688–701.
URL: *http://linkinghub.elsevier.com/retrieve/pii/S0377221709000575*

Tonge, F. M. (1961). *A heuristic program for assembly line balancing.*, Prentice-Hall., Englewood Cliffs, NJ.